

PDS #5724
PRODUCT INFORMATION



1191 Wheeling Road, Wheeling, IL 60090
Phone: 847-541-9000 Fax: 847-541-7549



168215 Valspar American Tradition Interior Latex Multi-Purpose Primer

PRODUCT: 168215 White

DESCRIPTION:

Valspar American Tradition® Interior Latex Multi-Purpose Primer

FEATURES:

American Tradition Multi-Purpose Primer is a white pigmented primer / sealer formulated for sealing surfaces and stains prior to topcoating. The water-base formula is low odor - an ideal feature for indoor uses.

WHERE TO USE:

Use indoors or outdoors to seal stains such as watermarks, smoke damage, surface burns, graffiti, lipstick, grease, rust stains, tannin bleed and mildew stains. Ideal for use over properly prepared wood, drywall, plaster, metal and masonry.

SURFACE PREPARATION:

General: Clean and dry surface thoroughly. Scrub stained areas with an all-purpose cleaner to remove any residual stains. Remove all surface dirt, chalk and mildew. Tannin stained areas on wood do not need special surface preparations.

For fire damaged areas, remove burned or severely charred areas to sound wood surface. Sand smooth. For mildew stains, this product will seal residual stains from old mildew, but will not resist active mildew growth. All active mildew must be removed from surfaces prior to application by scrubbing affected area with a commercial mildew remover or a solution of 1 part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Wear protective goggles and rubber gloves to avoid chemical contact with skin or eyes.

Previously Painted Surfaces: Scrape, sand, then prime. Dull glossy surfaces with gloss remover or sandpaper.

Metal: This product will seal rust stains on previously painted surfaces and provide an excellent bond for finish coats. It is not, however, formulated to be an anti-rust primer. To fully protect bare iron and steel surfaces from rust, prime with a rust inhibiting oil metal primer.

TYPICAL PRODUCT PROPERTIES:

(168215)

VEHICLE TYPE: Acrylic Resin
SOLIDS: 51% WT. 40% VOL.
VOC: 200 g/l max
WT/GAL: 10.4 lbs.
VISCOSITY: 93-101 KU
FLASHPOINT: N/A
60° GLOSS: 30-40 Units

COVERAGE / THINNING:

One gallon covers up to 400 sq. ft. (37.2 m²) depending upon surface porosity. Thin only for spray application with up to 8 oz. of water per gallon of paint.

FILM THICKNESS: 4.0 mil Wet
1.6 mil Dry

DRY TIMES:

Apply only when air and surface temperatures are between 50-90°F (10-32°C). Dries to the touch in 30 minutes. Allow to dry 2 hours before applying finish coat.

APPLICATION:

Stir thoroughly before and during use. Apply with a premium quality polyester brush, "one coat" roller or airless sprayer. If applying by sprayer, back-roll or back-brush to work primer into the surface. Apply a liberal coat of primer uniformly, working well into the surface. Allow to dry at least 2 hours before applying a latex topcoat, 4 hours for oil topcoats.

TINTING:

To enhance the appearance of the finish coat, tint the primer with Universal Tinting Colorants to a shade similar to the finish coat. Do not use more than 4 oz. of tinting color per gallon.

CLEAN UP:

Clean up with warm, soapy water.

PACKAGING:

Gallons & Quarts	4 Pack
5 Gallon Pails	Each

STORAGE AND DISPOSAL:

Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

**Product Information Hotline:
1-888-313-5569**

TYPICAL ANALYSIS: 168215

C.A.S. NO.	INGREDIENTS
7732-18-5	Water
25035-69-2	Acrylic Resin
13463-67-7	Titanium Dioxide
1314-13-2	Calcium Carbonate
1314-13-3	Ethylene Glycol
1314-13-4	Zinc Oxide Pigment
14808-60-7	Crystalline Silica

CAUTIONS:

CONTAINS CRYSTALLINE SILICA

May cause eye and skin irritation. Avoid breathing spray mist dust or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

AVOID CONTACT WITH THE EYES AND SKIN. Wash thoroughly after use. Close container after each use.

WARNING: This product contains a chemical known to the State of California to cause cancer.

FIRST AID:

EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.**

IF INHALED: If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.**

IF SWALLOWED: Drink 2 glasses of water. **Get medical attention immediately.**

Delayed effect from long-term exposure: Cancer Hazard. Contains crystalline silica which can cause cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist.

**DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN.**
For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

**This product contains less than
200 g/L VOC (1.7 lb./Gal VOS)**

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.