



SHOWERS AND TUBS TO BE PROVIDED WITH PRESSURE BALANCE OR THERMOSTATIC VALVES. ADJUST VALVES TO DELIVER MAX. 120 DEGREE WARM WATER, TYP.

SHOWERS AND TUBS TO BE PROVIDED WITH PRESSURE BALANCE OR THERMOSTATIC VALVES. ADJUST VALVES TO DELIVER MAX. 120 DEGREE WARM WATER, TYP.

HOSE BIB WITH NON-REMOVABLE BACK-FLOW DEVICE, TYP.

45'-6" MAXIMUM BUILDING AREA

24'-6" MIN. REQUIRED REAR YARD

1  
A-6

3

2  
A-6

2  
A-7

2  
A-3

PL

PL

ONE LINE  
1/7' ELEV  
OF P/L

1

2

3

4

5

A-7

1

2

3

4

5

4

5

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6

7

8

9

4

5

6